



A silent (no fan and a Solid State Disk), compact and low power solution for all the connection needs of a Branch of a Qmatic Orchestra system.

With Hub you get the option to isolate the Qmatic equipment on a separate LAN. In this way, the Qmatic LAN and the client's WAN are kept separate with the help of a firewall.

Hubs are placed in local Branches and communicate with the central server and all the Qmatic hardware at the local site, for example printers and displays.

If the Queue Agent is run in Hub: Should communication with the Orchestra server be lost, Hub can still run a local copy of the system for up to 24 hours.

Hub is driven by the QMX6/DC-2G eMMC4 QMA2 from Congatec.


Features

- Safe communications: the Qmatic LAN and the client's WAN are kept separate with the help of a firewall.
- Easy to setup and configure.
- Silent operation.
- Remote management.
- Media Player functionality.
- Voice Unit functionality (only supported by Orchestra).


With the Branch Hub, you can


- Support standalone operation for up to 24 hours.
- If network connection fails, continue the operation and synchronise the data and configuration once network connection is re-established.
- In a safe way, manage all the communication needs between the Qmatic equipment at a Branch and the Qmatic Orchestra central server.

| | | |
|---------------------------------|--------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Used with | Qmatic Orchestra and Solo* | |
| | *Voice Unit functionality is <i>not</i> supported by Solo! | |
| Technical specifications | Dimensions: L x W x H | 235 x 135 x 40 mm / 9.25 x 5.31 x 1.57 in |
| | Weight | 1095 g / 38.625 oz |
| | External power supply | 24V 2,5A |
| | Operating temperature | 10 – 40°C / 50 – 104°F |
| | Storage temperature | 0 – 40°C / 32 – 104°F |
| | Operating humidity | 15 – 75% R.H |
| | Storage humidity | 10 – 90% R.H |
| | Safety and other regulations | EMC, CE, RoHS, WEEE, REACH |
| | Maximum media storage capacity, for Queue Agent (on SD card) | 7 GB |
| | Video Formats | .webm .mp4 |
| | Sound file Formats | Opus Audio (.opus) WebM Audio (.weba) Ogg Vorbis (.ogg) Wave file (.wav) |
| The package contains | Hub | 1 |
| Available Power Cords | 11040308 | Power Cord EU |
| | 11040309 | Power Cord UK |
| | 11040310 | Power Cord USA |
| Article numbers | Hub | 10216100 |
| | Base License | 10115400 |
| | Network Gateway License | 10115401 |
| | Note: Not needed if running FW version 130.4.4.0, or later! | |
| | Distributed Logic Node License | 10115402 |
| | Media Player License (includes Announcement functionality) | 10115403 |
| Accessories | Lock, cables and USB | 10216220 |
| | 19" rack mount | 10216210 |
| | VESA mount | 10216200 |



*Intro 17 G2 comes with a built-in Hub and can, if wanted, replace the Hub in the centre of the picture.





Note: This functionality is only supported by Orchestra. For Solo, please use Choral.